

# KEENAN<sup>®</sup>

## VA2-24L



The KEENAN VA2-24L is the longer option in the KEENAN VA 24m<sup>3</sup> range of machines. The KEENAN VA2-24L is mounted on a heavy-duty chassis and features a robust gear box. This machine has a lower profile than the VA2-24S, giving the ability to be used on farms with height restrictions.



# VA2-24L

	Height	Width
VA2-24L	2,970mm (117")	2,500mm (98.5")
Mix Capacity	24m <sup>3</sup>	
Horsepower *	82-110 HP	

\*Power requirement dependent on loaded products

Fitted with KEENAN InTouch technology as standard the VA2-24L offers a greatly optimised nutritional output thanks to the unique algorithms guiding the exact mixing order, speed and number of rotations per load.



## SPEED

Materials are rapidly and efficiently mixed into the overall TMR

## CAPACITY

Efficient use of space to maximise capacity

## FOOTPRINT AND HANDLING

Extremely manoeuvrable. Small footprint allowing access to most farmyard buildings

## HEAVY DUTY CHASSIS

Mounted on custom-built heavy duty chassis to ensure durability under the toughest conditions

## SPRINT PADDLES

Sprint paddles help to speed up feed-out. One is fitted to each auger ensuring a constant rate of discharge of material.

## HEAVY DUTY AUGER AND BLADES

Fitted with heavy duty augers as standard. Triangular blades fitted with tungsten coating to increase longevity

## TWO-SPEED GEARBOX

The two-speed gearbox means that using low speed the power requirement from the tractor to start up a load is greatly reduced; while high speed can be used to ensure rapid, even emptying.

**KEENAN New Zealand**  
A division of JK Engineering  
Freephone: 0800 4 KEENAN  
Phone: 07 887 4994  
Jon: 027 2415 816  
admin@keenanz.co.nz

**KEENAN**<sup>®</sup>  
an **Alltech** company

keenansystem.com

 KEENAN System

 @KEENANsystem