

# KEENAN<sup>®</sup>

## VA2-24S



The VA2-24S is the shorter option in the KEENAN VA 24m<sup>3</sup> range and is ideally suited for situations where space is limited and mobility is of prime importance. As with all machines of the KEENAN VA range, it comes with KEENAN InTouch as standard to optimise the mix through implementing our unique algorithms for the exact mixing order, speed and number of rotations per load.



# VA2-24S

	Height	Width*
VA2-24S	3,320mm (131")	2,480mm (98")
Mix Capacity	24m <sup>3</sup>	
Horsepower **	70-95 HP	

\*Width VA2-24S with Cross Conveyor

\*\*Power requirement dependent on loaded products

Fitted with KEENAN InTouch technology as standard the VA2-24L offers a greatly optimised nutritional output thanks to the unique algorithms guiding the exact mixing order, speed and number of rotations per load.



## SPEED

Materials are rapidly and efficiently mixed into the overall TMR

## CAPACITY

Efficient use of space to maximise capacity

## FOOTPRINT AND HANDLING

Extremely manoeuvrable. Small footprint allowing access to most farmyard buildings

## HEAVY DUTY CHASSIS

Mounted on custom-built heavy duty chassis to ensure durability under the toughest conditions

## SPRINT PADDLES

Sprint paddles help to speed up feed-out. One is fitted to each auger ensuring a constant rate of discharge of material.

## HEAVY DUTY AUGER AND BLADES

Fitted with heavy duty augers as standard. Triangular blades fitted with tungsten coating to increase longevity

## TWO-SPEED GEARBOX

The two-speed gearbox means that using low speed the power requirement from the tractor to start up a load is greatly reduced; while high speed can be used to ensure rapid, even emptying.

**KEENAN New Zealand**  
A division of JK Engineering  
Freephone: 0800 4 KEENAN  
Phone: 07 887 4994  
Jon: 027 2415 816  
admin@keenanz.co.nz

**KEENAN**<sup>®</sup>  
an **Alltech** company

keenansystem.com

KEENAN System

@KEENANsystem