

KEENAN[®]

VA2-30



The KEENAN VA2-30 is a heavy-duty machine with the capacity to feed large herds quickly. Multiple feed-out options to suit a variety of feeding situations are available with this machine. This applies to the full range of the KEENAN VA machines.

VA2-30

	Height	Width
VA2-30	3,340mm (131.5")	2,500mm (98.5")
Mix Capacity	30m ³	
Horsepower *	104-140 HP	

*Power requirement dependent on loaded products

Fitted with KEENAN InTouch technology as standard the VA2-24L offers a greatly optimised nutritional output thanks to the unique algorithms guiding the exact mixing order, speed and number of rotations per load.



SPEED

Materials are rapidly and efficiently mixed into the overall TMR

CAPACITY

Efficient use of space to maximise capacity

FOOTPRINT AND HANDLING

Extremely manoeuvrable. Small footprint allowing access to most farmyard buildings

HEAVY DUTY CHASSIS

Mounted on custom-built heavy duty chassis to ensure durability under the toughest conditions

SPRINT PADDLES

Sprint paddles help to speed up feed-out. One is fitted to each auger ensuring a constant rate of discharge of material.

HEAVY DUTY AUGER AND BLADES

Fitted with heavy duty augers as standard. Triangular blades fitted with tungsten coating to increase longevity

TWO-SPEED GEARBOX

The two-speed gearbox means that using low speed the power requirement from the tractor to start up a load is greatly reduced; while high speed can be used to ensure rapid, even emptying.

KEENAN New Zealand
A division of JK Engineering
Freephone: 0800 4 KEENAN
Phone: 07 887 4994
Jon: 027 2415 816
admin@keenanz.co.nz

KEENAN[®]
an **Alltech** company

keenansystem.com

KEENAN System

@KEENANsystem